

# ONE-PIECE FIELD CORE SHELL

## FIELD OF THE INVENTION

This invention relates generally to a field core shell typically part of a field core assembly used on an electromagnetic clutch of the type found in automotive air conditioning systems to drive a compressor, and more particularly, to a one-piece field core shell and method of shaping the one-piece field core shell by spin-roll forming.

## BACKGROUND OF THE INVENTION

A typical electromagnetic clutch contains an annular electromagnet coil that fits into a wire winding pod section in the field core shell of a field core assembly.

Field core shells have traditionally been manufactured using a two-piece construction. As shown in FIGS. 1A-C, a press formed top angled piece is attached to a press formed annular bottom piece that contains inner and outer rings used to hold the wire windings of the electromagnetic coil. As illustrated in Patent No. 5,273,385, incorporated by reference, an integral blind tubular rivet is used to hold the top angled piece to the bottom piece, forming the completed assembly. This assembly is illustrated in cross-section in FIG. 1C.

Forming a field core shell from a two-piece construction described above and as shown in FIG. 1C is a time consuming and costly process.

1 The cost of manufacturing two separate components that comprise the  
2 shell and the cost of assembling those components, may be reduced by  
3 forming a one-piece shell.

4 References in the automotive art that disclose spin-roll forming  
5 products from a single piece of metal include U.S. Patents No. 4,388,817,  
6 No. 4,532,786, and No. 4,936,129. Each of these patents discloses a  
7 method of forming an automotive wheel from a single piece of metal  
8 wherein, during the wheel-forming process, a peripheral portion of the  
9 metal preform is split radially to form two annular split portions, which are  
10 then formed into different portions of the wheel rim.

11 The present invention relates to manufacturing a one-piece field  
12 core shell by using spin-roll forming methods. A one-piece field core shell  
13 that may be used in a field core assembly such as those found on an  
14 electromagnetic clutch of the type found in automotive air conditioning  
15 systems.

## 16 SUMMARY OF THE INVENTION

17 In accordance with one aspect, the present invention provides for a  
18 field core shell made from a single piece of metal typically, a solid circular  
19 disk, by a spin-roll forming process. The spin-roll forming process displaces  
20 metal from a flat portion (e.g., a flat plate of metal sheet) in a radial and  
21 axial direction to produce the one-piece field core shell.

1 In accordance with another aspect, the present invention provides  
2 a spin-roll formed one-piece field core shell that is formed from a disc  
3 having top and bottom external surfaces. The core shell has an outer  
4 annular ring integral to and encircling a center axis of the disc and  
5 extending from the bottom external surface in a direction that is  
6 perpendicular to the bottom surface of the disc and parallel to the center  
7 axis of the disc. The core shell has an inner annular ring integral to and  
8 encircling a center axis of the disc, with the inner annular axis spaced  
9 radially inward from the outer annular ring and extending from the bottom  
10 external surface in a direction that is perpendicular to the bottom surface  
11 of the disc and parallel to the center axis of the disc. The core shell also  
12 has a mounting flange integral to the disc, with having a bore extending  
13 from the mounting flange to the bottom external surface of the disc.

14 In accordance with yet another aspect, the present invention  
15 provides a method of forming the one-piece field core shell. In the  
16 method, a shaping roller is pressed against a side of a spinning annular  
17 disc of sheet metal. The shaping roller is moved progressively radially  
18 inwardly against the side of the rotating disc which displaces a portion of  
19 metal in the form of an axially extending annular wave. The so displaced  
20 metal is pressed by an axially moving shaping roller against different  
21 mandrels to form a mounting flange and two annular rings opposite the  
22 mounting flange to complete the integral one-piece component.

1 A feature of the invention is to provide a field core shell that is made  
2 from a one-piece construction that is less costly and time consuming to  
3 manufacture than the current construction.

#### 4 **BRIEF DESCRIPTION OF THE DRAWINGS**

5 FIG. 1A is a top perspective view of a prior art field core shell;

6 FIG. 1B is a bottom perspective view of the core shell of FIG. 1A, and  
7 shows installed wire windings;

8 FIG. 1C is a cross section view taken along line 1C-1C in FIG. 1A;

9 FIG. 2A is a top perspective view of a first embodiment of a field  
10 core shell of the present invention;

11 FIG. 2B is a bottom perspective view of the first embodiment of the  
12 field core shell of the present invention;

13 FIG. 2C is a cross section view taken along line 2C-2C in FIG. 2A;

14 FIG. 3A is a top perspective view of a second embodiment of the  
15 field core shell of the present invention;

16 FIG. 3B is a bottom perspective view of the second embodiment of  
17 the field core shell of the present invention;

18 FIG. 3C is a cross section view taken along line 3C-3C in FIG. 3A;

19 FIG. 4A is a cross section view of a stamped wire winding pod that  
20 may be used to make either a first or second embodiment of the field  
21 core shell of the present invention;

1 FIG. 4B is a cross section view of the first embodiment of the field  
2 core shell made using the stamped wire winding pod in FIG. 4A, with the  
3 mounting flange being spin-roll formed;

4 FIG. 5 is a cross-section view of key elements of a spin-roll forming  
5 machine and an annular disc positioned in the machine for spin-roll  
6 forming;

7 FIG. 6 is a view similar to FIG. 5, but showing a machine at a  
8 progressive operational step completing the mounting flange in the first  
9 embodiment of the field core shell of the present invention;

10 FIG. 7 is a view similar to FIG. 5, but showing the machine at a  
11 progressive operational step completing the inner annular ring of the first  
12 embodiment of the field core shell of the present invention;

13 FIG. 8 is a view similar to FIG. 5 but showing the machine at a  
14 progressive operational step the outer annular ring of the first embodiment  
15 of the field core shell of the present invention;

16 FIG. 9 illustrates the completion of the bore and a hole for wire leads  
17 for the first embodiment of the field core shell of the present invention;  
18 and

19 FIGS. 10-13 are cross-section views that illustrate a second method  
20 for making the first embodiment of the field core shell of the present  
21 invention.

## DETAILED DESCRIPTION OF THE EXAMPLE EMBODIMENTS

In order to better appreciate the present invention, the prior art is briefly discussed. Referring now to FIG. 1A-C, a prior art two-piece field core shell **10a** is shown having an outer annular ring **26a** and an inner annular ring **24a** that form a wire winding pod **20a**. Using multiple components, a separately formed mounting flange **30a** is attached to the wire winding pod **20a** by rivets **14a** using a number of manufacturing operations.

A first embodiment of a one-piece field core shell **10** shown in FIGS. 2A-C is produced from a blank disc of sheet metal. The first embodiment includes a spin-roll formed wire winding pod **22** having an outer annular ring **26**, an inner annular ring **24** and a top surface **25**. The top surface **25** having a hole **18** to feed wire leads. The mounting flange **30** is spin-roll formed completing the one-piece field core shell **10** of the first embodiment of the present invention.

A first method for forming the first embodiment of the present invention formed from a blank disc of sheet metal is shown in progressive steps in FIGS. 5-9 and will now be described.

Referring to FIG. 5, a spin-roll forming machine **40** is shown in an initial run position where the blank disc is starting to be shaped in a form that, when finished, includes the features of the first embodiment of the present invention.

1 Machine **40** is a versatile piece of equipment that can  
2 accommodate mandrels that may form a range of mounting flanges and  
3 wire winding pod diameters according to the methods of the present  
4 invention. Mandrels are selected and used having the required  
5 corresponding diameters needed to form the appropriate mounting  
6 flanges and wire winding pods as desired by the field core shell machine  
7 operator.

8 The machine **40** includes a headstock mandrel **42** and a mounting  
9 flange forming mandrel **44**. A solid circular disc **50** of sheet metal is  
10 positioned within a circular recess **56** on the headstock mandrel **42** and is  
11 securely clamped thereto by an end face **46** of mounting flange forming  
12 mandrel **44**. The mounting flange forming mandrel **44** is moved in an axial  
13 direction D and pressed firmly against the center of disc **50** to hold it in  
14 position during the forming process.

15 A shaping roller **48** is transferred to an initial forming position by  
16 moving it in the X direction so that a rounded edge **49** of the shaping roller  
17 is pressed against the disc **50**. The mandrel and head stock are rotated  
18 which spins the disc around an axis A. Shaping roller **48** is also free to  
19 rotate around axis B as the disc spins. The shaping roller **48** with its  
20 rounded edge **49** moves progressively in direction X from edge **54** (FIG. 5)  
21 against the upper face **52** of the disc and displaces metal along the  
22 upper face of the disc and thins the disc while forming mounting flange **30**

1 (FIG.6) to a desired height and diameter, for example, as is shown in FIG.  
2 6.

3 The one-piece field core shell, with its mounting flange **30** formed, is  
4 taken from the mandrel **42** and inverted 180 degrees and placed onto a  
5 mounting flange mandrel **44** (FIG. 7). The mounting flange mandrel **44**  
6 holds the partially formed one-piece field core for its next operation. As  
7 shown in FIG. 7, the inner annular ring **24** is now spin-roll formed by shaping  
8 roller **48**. Mounting flange **30** is pressed firmly into mounting flange  
9 mandrel **44**, while the partially formed one-piece field core shell is securely  
10 clamped by end face **63** of inner annular ring forming mandrel **62**.  
11 Mounting flange **30** spins about axis A in spin-roll forming machine **40** while  
12 the shaping roller **48** is again, as shown in FIG. 5, brought into contact with  
13 an upper face **52** of disc **50** at a position proximate the edge **54** of disc **50**.  
14 The shaping roller **48**, with its rounded edge **49**, moves progressively in  
15 direction X against the side of the disc and displaces metal from the side  
16 of the disc and thins the disc while forming the inner annular ring **24** to a  
17 desired height and diameter, for example as shown in FIG. 7.

18 Once the inner annular ring **24** is formed, the one-piece field core  
19 shell is ready for its final operations. (FIGS. 8 and 9). The one-piece field  
20 core shell with its mounting flange **30** and inner annular ring **24** formed, is  
21 taken from mandrel **44** and again inverted 180 degrees and placed onto  
22 outer annular ring mandrel **61**(FIG. 8). Mandrel **44** and outer annular ring  
23 mandrel **61** hold the part in spin-roll forming machine **40** while outer



1 annular ring forming tool **64** moves in the X direction contacting edge **58**  
2 as shown in FIG. 7, moving edge **58** in the D direction forming outer  
3 annular ring **26** to a desired height and diameter, for example as shown in  
4 FIG. 8.

5 As shown in FIG. 9, the bore **16**, used to mount a shaft (not shown)  
6 and access hole **18** for the lead wires of the wire windings are then formed  
7 using tools **35, 36**. The tools may be devices such as a drill or punch or any  
8 other tool that can pierce sheet metal. The above-described method of  
9 forming the first embodiment from a blank disc of sheet metal thus  
10 produces the less costly and easily manufactured spin-roll formed field  
11 core shell of the present invention.

12 A second method of forming the first embodiment is shown in FIGS.  
13 10-13. An annular disc **51** with a center hole **57** is placed in machine **40** as  
14 shown in FIG. 10. A mounting flange **30** and bore is formed using tool **33**  
15 by the application of force to a desired height and diameter, for example,  
16 as shown in FIG. 11.

17 As shown in FIG. 12, the inner annular ring **24** is now spin-roll formed  
18 by shaping roller **48**. Mounting flange **30** is pressed firmly into mounting  
19 flange mandrel **44**, while the partially formed one-piece field core shell is  
20 also securely clamped in inner annular ring forming mandrel **62**.  
21 Mounting flange **30** spins about axis A in spin-roll forming machine **40** while  
22 the shaping roller **48** is brought into contact with an upper face **52** of disc  
23 **51** at a position proximate the edge **54** of disc **51**. The shaping roller **48**,

1 with its rounded edge **49**, moves progressively in direction X against the  
2 side of the disc and displaces metal from the side of the disc and thins the  
3 disc while forming the inner annular ring **24** to a desired height and  
4 diameter, for example, as shown in FIG. 12.

5 Once the inner annular ring **24** is formed, the one-piece field core  
6 shell is ready for its final operation (FIG. 13). The one-piece field core shell  
7 with its mounting flange **30** and inner annular ring **24** formed, is taken from  
8 mandrel **44** and inverted 180 degrees and placed onto outer annular ring  
9 mandrel **61** (FIG. 13). Mandrel **44** and outer annular ring mandrel **61** hold  
10 the part in spin-roll forming machine **40** while outer annular ring forming  
11 tool **64** moves in the X direction contacting edge **58** (FIG. 12), moving  
12 edge **58** in the D direction forming outer annular ring **26** to a desired  
13 height and diameter, for example, as shown in FIG. 13. Similar to the  
14 process step in FIG. 9, the access hole **18** for the leads for the wire winding  
15 is then formed using tool **36**.

16 The first embodiment of the one-piece field core shell **10** of the  
17 present invention as shown in FIGS. 2A-C, may also be produced by using  
18 a pre-stamped wire winding pod **21** as shown in FIG. 4A. The stamped  
19 wire winding pod **21** has outer annular ring **26** and inner annular ring **24**  
20 already formed. Stamped wire winding pod **21** is made in a separate  
21 operation and is used in place of the spin-roll formed wire winding pod **22**.  
22 The stamped wire winding pod **21** as shown in FIG. 4B, is placed in machine  
23 **40** and as explained below, the mounting flange **30** is spin-roll formed to a

1 desired height and diameter, for example, as shown in FIG. 4B. A bore **16**  
2 and access hole **18** for the lead wires of wire windings are also added as  
3 shown in FIGS. 2A and 2C.

4 The method for forming the first embodiment using the stamped  
5 wire winding pod **21** of the present invention will now be described with  
6 reference to FIG. 4B. The stamped wire winding pod **21** having a top  
7 surface **28** is positioned in the spin-roll forming machinery **40** that includes  
8 the mounting flange mandrel **44**, a stamped wire winding pod mandrel **41**  
9 and a shaping roller **48**. The shaping roller **48** with its rounded edge **49**  
10 displaces a portion of metal from the top surface **28** of the stamped wire  
11 winding pod **21** which is supported in mandrel **41**.

12 The shaping roller **48** is transferred to an initial forming position by  
13 moving it in direction X so that a rounded edge **49** of the shaping roller is  
14 pressed against the disc. The shaping roller **48** with its rounded edge **49**  
15 moves progressively in direction X against the top surface **28** of the disc  
16 and displaces metal along the upper face of the disc and thins the disc  
17 while forming mounting flange **30** to a desired height and diameter, for  
18 example, as is shown in FIG. 4B. Similar to the process step in FIG. 9, the  
19 bore **16** and access hole **18** for the leads for the wire windings are formed.

20 Referring now to FIGS. 3A-C, a second embodiment of the one-  
21 piece field core shell **11**, has a mounting flange that extends parallel to  
22 the top surface **34**. The second embodiment is also produced from a  
23 blank sheet of sheet metal. The second embodiment includes a spin-roll

1 formed wire winding pod **22**, having an outer annular ring **26** and an inner  
2 annular ring **24** and holes **18, 19** on the top surface **34** to feed wire leads.

3 A method for forming the second embodiment of the one-piece  
4 field core, as discussed in the paragraph immediately above, follows in  
5 the paragraph below. The equipment and methods used to form the  
6 second embodiment are similar to the equipment and methods used to  
7 form the first embodiment as previously described and illustrated by FIGS.  
8 5-13. The description of the method used to form the second  
9 embodiment below will not include any reference to any particular figures  
10 cited above.

11 To form the second embodiment, the spin-roll forming machine **40**  
12 first utilizes the inner annular ring forming mandrel **62**. A solid circular disc  
13 **50** of sheet metal is positioned within a circular recess **56** on the headstock  
14 mandrel **42** and is securely clamped thereto by an end face **46** of inner  
15 annular ring forming mandrel **62**. The inner annular ring forming mandrel  
16 **62** is moved in an axial direction D and pressed firmly against the center of  
17 disc **50** to hold it in position during the forming process.

18 A shaping roller **48** is transferred to an initial forming position by  
19 moving it in direction X so that a rounded edge **49** of the shaping roller is  
20 pressed against the disc. The mandrel and head stock are rotated which  
21 spins the disc around an axis A. Shaping roller **48** is also free to rotate as  
22 the disc spins. The shaping roller **48** with its rounded edge **49** moves  
23 progressively in direction X from edge **54** against the upper face **52** of the

1 disc and displaces metal along the upper face of the disc and thins the  
2 disc while forming inner annular ring **24** to a desired height and diameter.

3 Once the inner annular ring **24** is formed, the second embodiment  
4 of the one-piece field core shell is ready for the outer annular ring **26** to be  
5 formed. The one-piece field core shell with its inner annular ring **24**  
6 formed, is taken from mandrel **44** and inverted 180 degrees and placed  
7 onto outer annular ring mandrel **61**. Mandrel **44** and outer annular ring  
8 mandrel **61** hold the part in spin-roll forming machine **40** while outer  
9 annular ring forming tool **64** moves in the X direction contacting edge **58**,  
10 moving edge **58** in the D direction forming outer annular ring **26** to a  
11 desired height and diameter.

12 Once the outer annular ring **26** is formed, the second embodiment  
13 of the one-piece field core shell is ready for its final operation. The center  
14 of the circular disk is removed, forming a mounting flange **32** as shown in  
15 FIG. 3A. Also similar to the process step in FIG. 9, the access holes **18, 19**  
16 for the leads for wire winding are formed.

17 The inner and outer annular rings of each embodiment of the field  
18 core shell as described, may be tapered at an angle alpha (FIG. 2C) in  
19 order to allowing the wire windings to enter the wire winding pod formed  
20 by the field core shell's annular rings. The tapered angle alpha may be  
21 from 0 to 3 degrees from an axis that is parallel to the center axis A of the  
22 field core shell as shown in FIG. 2C.

1 In addition, the inner and outer annular rings of each embodiment  
2 of the field core shell as described, extend in a direction that is  
3 perpendicular to the bottom surface of the disc and parallel to the center  
4 axis of the disc and may be the same distance or one ring may extend  
5 farther than the other in length in order to completely capture the wire  
6 windings once installed in the field core shell's wire winding pod.

7 It will be understood by one who is skilled in the art of field cores that  
8 a range of mounting flanges and wire winding pod diameters can be  
9 provided according to the methods of the present invention by selecting  
10 mandrels having the required corresponding diameters to the appropriate  
11 mounting flanges and wire winding pods desired.

12 It is also understood by one who is skilled in the art of spin-roll  
13 forming that the order of steps taken to spin-roll form may be reduced or  
14 altered from those described above to produce the equivalent one-piece  
15 field core shell of the present invention. Also, many types of forming  
16 methods equivalent to the spin-roll forming method may be used to  
17 produce the desired one-piece field core shell of the present invention.  
18 The present invention includes all such equivalent steps and forming  
19 methods, and is limited only by the scope of the claims.

20 Although the invention has been shown and described with respect  
21 to certain embodiments, it is obvious that equivalent alterations and  
22 modifications will occur beyond those discussed to others skilled in the art  
23 upon reading and understanding of the specification. The present

- 1 invention includes all such equivalent alterations and modifications, and is
- 2 limited only by the scope of the claims.

11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000